

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Carbon dioxide (solid)

Date of issue: 21/03/2015 Supersedes: 01/07/2015 Revision date: 10/01/2017 Version: 2.1

SDS reference: RS-CO2-018C

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Carbon dioxide (solid)
SDS no : RS-CO2-018C
Chemical description : Carbon dioxide (solid)

CAS No : 124-38-9 EC No : 204-696-9 EC Index No : ---

Registration-No. : Listed in Annex IV / V REACH, exempted from registration.

Chemical formula : CO2

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use

Cooling (Food additive E290)

Blast cleaning Metal cooling

Contact supplier for more information on uses

### 1.3. Details of the supplier of the safety data sheet

Company identification : Messer Tehnogas AD

Banjicki put 62

11090 Beograd Serbia +38 111 353 7210

1.4. Emergency telephone number

Emergency telephone number : +381(0) 11 360 8440 (24h)

Emergency telephone number

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not regulated.

Full text of H-statements see section 16.

### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

### 2.3. Other hazards

: Asphyxiant in high concentrations

Refrigerated solidified gas. Contact with product may cause cold burns or frostbite

1/9

# **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Name Product identitier %			1	Oleanida di ancara di ancara la Description
Name Folder Identifier /6 (EC) No. 1272/2000 I	Namo	Product identifier	0/_	Classification according to Regulation
(EC) NO. 1212/2000	Name	i ioduct identiliei	/6	(EC) No. 1272/2008 [CLP]

Messer Tehnogas AD EN (English) SDS Ref.: RS-CO2-018C
Banjicki put 62 11090 Beograd Serbia



SDS Ref.: RS-CO2-018C

Carbon dioxide (solid)	(CAS No) 124-38-9 (EC No) 204-696-9 (EC Index No) (Registration-No.) *1	100	Not classified
------------------------	--	-----	----------------

Contains no other components or impurities which will influence the classification of the product.

- \*1: Listed in Annex IV / V REACH, exempted from registration.
- \*2: Registration deadline not expired.
- \*3: Registration not required: Substance manufactured or imported < 1t/y.

Full text of H-statements see section 16.

3.2. Mixtures : Not applicable

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped

- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain

medical assistance

- Eye contact : Adverse effects not expected from this product

- Ingestion : Get immediate medical attention

### 4.2. Most important symptoms and effects, both acute and delayed

 In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation Low concentrations of CO2 cause increased respiration and headache

### 4.3. Indication of any immediate medical attention and special treatment needed

: None

## **SECTION 5: Fire-fighting measures**

### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog

- Unsuitable extinguishing media : Do not use water jet to extinguish

### 5.2. Special hazards arising from the substance or mixture

Specific hazards : None Hazardous combustion products : None

5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat

radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and

drainage systems

Use water spray or fog to knock down fire fumes if possible

EN (English)

SDS Ref.: RS-CO2-018C



SDS Ref.: RS-CO2-018C

Special protective equipment for fire fighters

: Use self-contained breathing apparatus

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask

Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for

firefighters

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

: Evacuate area

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to

be safe

Use protective clothing

Ensure adequate air ventilation

Act in accordance with local emergency plan

Stay upwind

### 6.2. Environmental precautions

: Prevent from entering sewers, basements and workpits, or any place where its accumulation

can be dangerous

### 6.3. Methods and material for containment and cleaning up

: Ventilate area

### 6.4. Reference to other sections

: See also sections 8 and 13

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Safe use of the product : The product must be handled in accordance with good industrial hygiene and safety

procedures

Refer to supplier's container handling instructions

Do not smoke while handling product

Use only properly specified equipment which is suitable for this product, its supply pressure and

SDS Ref.: RS-CO2-018C

temperature. Contact your gas supplier if in doubt

Do not breathe gas.

### 7.2. Conditions for safe storage, including any incompatibilities

: Observe all regulations and local requirements regarding storage of containers

Keep container below 50°C in a well ventilated place.

### 7.3. Specific end use(s)

: None.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

Carbon dioxide (solid) (124-38-9)			
OEL: Occupational E	xposure Limits		
Austria	TWA (AT) OEL 8h [mg/m³]	9000 mg/m³	
	STEL (AT) OEL 15min [ppm]	10000 ppm (60' Mow / 3x)	
	STEL (AT) OEL 15min [mg/m³]	18000 mg/m³ (60' Mow / 3x)	
	TWA (AT) OEL 8h [ppm]	5000 ppm	
Belgium	TWA (BE) OEL 8h [mg/m3]	9131 mg/m³	
	TWA (BE) OEL 8h [ppm]	5000 ppm	
	STEL (BE) OEL 15min [mg/m3]	54784 mg/m³	



SDS Ref.: RS-CO2-018C

	STEL (BE) OEL 15min [ppm]	30000 ppm
Bulgaria	TWA (BG) OEL 8h [mg/m³]	9000 mg/m³
Cyprus	TWA (CY) OEL 8h [mg/m³]	9000 mg/m³
-71	TWA (CY) OEL 8h [ppm]	5000 ppm
Estonia	TWA (EE) OEL 8h [mg/m³]	9000 mg/m³
	TWA (EE) OEL 8h [ppm]	5000 ppm
France	TWA (FR) OEL 8h [mg/m³]	9000 mg/m³
0	TWA (FR) OEL 8h [ppm]	5000 ppm
Germany	TWA (DE) OEL 8h [mg/m3] TRGS 900 TWA (DE) OEL 8h [ppm] TRGS 900	9100 mg/m³ 5000 ppm
	Peak exposure limitation factor (DE) OEL TRGS 900	2
Greece	TWA (GR) OEL 8h [mg/m³]	9000 mg/m³
	TWA (GR) OEL 8h [ppm]	5000 ppm
	STEL (GR) OEL 15min [mg/m³]	54000 mg/m³
	STEL (GR) OEL 15min [ppm]	30000 ppm
Italy	TWA (IT) OEL 8h [mg/m³]	9000 mg/m³
	TWA (IT) OEL 8h [ppm]	5000 ppm
Latvia	TWA (LV) OEL 8h [mg/m³]	9000 mg/m³
	TWA (LV) OEL 8h [ppm]	5000 ppm
Spain	TWA (ES) OEL 8h [mg/m3]	9150 mg/m³
	TWA (ES) OEL 8h [ppm]	5000 ppm
Switzerland	TWA (CH) OEL 8h [mg/m³]	9000 mg/m³
Nathaulauda	TWA (CH) OEL 8h [ppm]	5000 ppm
Netherlands United Kingdom	MAC TWA 8H (NL) [mg/m³]  WEL - LTEL - UK [mg/m³]	9000 mg/m³ 9150 mg/m³
Officed Kingdom	WEL - LTEL - UK [ppm]	5000 ppm
	WEL - STEL - UK [mg/m³]	27400 mg/m³
	WEL - STEL - UK [ppm]	15000 ppm
Czech Republic	TWA (CZ) OEL 8h [mg/m³]	9000 mg/m³
	TWA (CZ) OEL 8h [ppm]	5000 ppm
	STEL (CZ) OEL 15min [mg/m³]	45000 mg/m³
	STEL (CZ) OEL 15min [ppm]	25000 ppm
		1 ''
Denmark	TWA (DK) OEL 8h [mg/m³]	9000 mg/m³
	TWA (DK) OEL 8h [ppm]	5000 ppm
Finland	TWA (FI) OEL 8h [mg/m³]	9100 mg/m³
	TWA (FI) OEL 8h [ppm]	5000 ppm
Hungary	TWA (HU) OEL 8h [mg/m3]	9000 mg/m³
Ireland	OEL (IE)-(8-hour reference period) [mg/m3]	9000 mg/m³
	OEL (IE)-(8-hour reference period) [ppm]	5000 ppm
	OEL (IE)-(15min reference period) [mg/m3]	27000 mg/m³
	, , ,	
	OEL (IE)-(15min reference period) [ppm]	15000 ppm
Lithuania	TWA (LT) OEL 8h [mg/m3]	9000 mg/m³
	TWA (LT) OEL 8h [ppm]	5000 ppm
Malta	TWA (MT) OEL 8h [mg/m³]	9000 mg/m³
	TWA (MT) OEL 8h [ppm]	5000 ppm
Norway	TWA (NO) OEL 8h [mg/m³]	9000 mg/m³
	TWA (NO) OEL 8h [ppm]	5000 ppm
Poland	TWA (PL) OEL 8h [mg/m³]	9000 mg/m³
	STEL (PL) OEL 15min [mg/m³]	27000 mg/m³
Pomonio	, ,	9000 mg/m³
Romania	TWA (RO) OEL 8h [mg/m³] TWA (RO) OEL 8h [ppm]	5000 mg/m <sup>2</sup>
Slovakia	Maximum permissible exposure limit, average, 8h (SK) [mg/m³]	9000 mg/m³
	Maximum permissible exposure limit, average, 8h (SK) [ppm]	5000 ppm
Sweden	TWA (SV) OEL 8h [mg/m³]	9000 mg/m³
	TWA (SV) OEL 8h [ppm]	5000 ppm
	STEL (SV) OEL 15min [mg/m³]	18000 mg/m³



SDS Ref.: RS-CO2-018C

	STEL (SV) OEL 15min [ppm]	10000 ppm
Portugal	TWA (PT) OEL 8h [ppm]	5000 ppm
	STEL (PT) OEL 15min [ppm]	30000 ppm

DNEL (Derived-No Effect Level): No data available.

PNEC (Predicted No-Effect Concentration): No data available.

### 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation

Ensure exposure is below occupational exposure limits (where available) Oxygen detectors should be used when asphyxiating gases may be released Consider the use of a work permit system e.g. for maintenance activities

### 8.2.2. Individual protection measures, e.g. personal protective equipment

: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The

following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected

Wear safety glasses with side shields · Eye/face protection

Standard EN 166 - Personal eye-protection - specifications

Skin protection

- Hand protection : Wear working gloves when handling gas containers

Standard EN 388 - Protective gloves against mechanical risk

: Wear safety shoes while handling containers - Other

Standard EN ISO 20345 - Personal protective equipment - Safety footwear

· Respiratory protection : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be

used in oxygen-deficient atmospheres

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask

· Thermal hazards : Wear cold insulating gloves

Standard EN 511 - Cold insulating gloves

8.2.3. Environmental exposure controls

: None necessary.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C / 101.3kPa : Gas

: Refrigerated solidified gas Physical state

· White Colour

Odour : No odour warning properties.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH value : Not applicable. Molar mass : 44 g/mol : 78.5 °C Melting point **Boiling point** : 56.6 °C (s)

Flash point : Not applicable for gases and gas mixtures.

Critical temperature [°C]

Evaporation rate (ether=1) : Not applicable for gases and gas mixtures.

EN (English) SDS Ref.: RS-CO2-018C Messer Tehnogas AD 5/9 Banjicki put 62 11090 Beograd Serbia



SDS Ref.: RS-CO2-018C

Flammability range : Non flammable.

Vapour pressure [20°C] : 57.3 bar(a)

Vapour pressure [50°C] : Not applicable.

Relative density, gas (air=1) : 1.52
Relative density, liquid (water=1) : 1.03

Solubility in water : 2000 mg/l Completely soluble.

Partition coefficient n-octanol/water [log Kow] : 0.83

Auto-ignition temperature : Not applicable.

Viscosity [20°C] : Not applicable.

Explosive Properties : Not applicable

Oxidising Properties : None

9.2. Other information

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level

### **SECTION 10: Stability and reactivity**

10.1. Reactivity

: None

10.2. Chemical stability

: Stable under normal conditions

10.3. Possibility of hazardous reactions

: None

10.4. Conditions to avoid

: None under recommended storage and handling conditions (see section 7)

10.5. Incompatible materials

: For additional information on compatibility refer to ISO 11114

10.6. Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be

produced

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity : In high concentrations C

: In high concentrations CO2 cause rapid circulatory insufficiency. Symptoms are headache, nausea and vomiting, which may lead to unconsciousness

Unlike simple asphyxiants, carbon dioxide has the ability to cause death even when normal oxygen levels (20-21%) are maintained. 5% CO2 has been found to act synergistically to increase the toxicity of certain other gases (CO, NO2). CO2 has been shown to enhance the production of carboxy- or met-hemoglobin by these gases possibly due to carbon dioxide's

stimulatory effects on the respiratory and circulatory systems

 Skin corrosion/irritation
 : No known effects from this product

 Serious eye damage/irritation
 : No known effects from this product

 Respiratory or skin sensitisation
 : No known effects from this product

 Germ cell mutagenicity
 : No known effects from this product

 Carcinogenicity
 : No known effects from this product

 Toxic for reproduction : Fertility
 : No known effects from this product

Toxic for reproduction : unborn child: No known effects from this productSTOT-single exposure: No known effects from this productSTOT-repeated exposure: No known effects from this product

Messer Tehnogas AD EN (English) SDS Ref.: RS-CO2-018C 6/9

Banjicki put 62 11090 Beograd Serbia

+38 111 353 7210



SDS Ref.: RS-CO2-018C

Aspiration hazard : Not applicable for gases and gas mixtures

### **SECTION 12: Ecological information**

12.1. Toxicity

Assessment : No ecological damage caused by this product.

12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

12.3. Bioaccumulative potential

Assessment : No ecological damage caused by this product.

12.4. Mobility in soil

Assessment : No ecological damage caused by this product.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB

12.6. Other adverse effects

: Can cause frost damage to vegetation.

Effect on the ozone layer : None Global warming potential [CO2=1] : 1

Effect on global warming : When discharged in large quantities may contribute to the greenhouse effect

### **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

Consult supplier for specific recommendations

Discharge to atmosphere in large quantities should be avoided

Do not discharge into any place where its accumulation could be dangerous : 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04

List of hazardous waste codes (from Commission Decision 2001/118/EC)

13.2. Additional information

: None

## **SECTION 14: Transport information**

### 14.1. UN number

UN-No. : 1845

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : Not regulated.

Transport by air (ICAO-TI / IATA-DGR) : CARBON DIOXIDE, SOLID

Transport by sea (IMDG) : CARBON DIOXIDE, SOLID (DRY ICE)

14.3. Transport hazard class(es)

 Messer Tehnogas AD
 EN (English)
 SDS Ref.: RS-CO2-018C
 7/9



SDS Ref.: RS-CO2-018C

Transport by road/rail (ADR/RID)

Class : 9 Classification code : M11

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 9

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 9
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable
Transport by air (ICAO-TI / IATA-DGR) : Not applicable
Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : None.

### 14.6. Special precautions for user

### Packing Instruction(s)

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 954
Cargo Aircraft only : 954
Transport by sea (IMDG) : P003

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

event of an accident or an emergency Before transporting product containers: - Ensure there is adequate ventilation - Ensure that containers are firmly secured.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU-Regulations**

Restrictions on use : None
Seveso Directive : 2012/18/EU (Seveso III) : Not covered

National regulations

National legislation : Ensure all national/local regulations are observed.

Water hazard class (WGK) : nwg - Non-hazardous to water

Kenn-Nr. : 256

Messer Tehnogas AD EN (English) SDS Ref.: RS-CO2-018C 8/9
Banjicki put 62 11090 Beograd Serbia

+38 111 353 7210



SDS Ref.: RS-CO2-018C

### 15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product

### **SECTION 16: Other information**

Indication of changes

: Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.

Training advice Further information : The hazard of asphyxiation is often overlooked and must be stressed during operator training.

: This Safety Data Sheet has been established in accordance with the applicable European

Union legislation.

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out

Details given in this document are believed to be correct at the time of going to press Whilst proper care has been taken in the preparation of this document, no liability for injury or

SDS Ref.: RS-CO2-018C

damage resulting from its use can be accepted

**End of document**